

CORRUGATING BELTS AND TRACTION BELTS

Reliable equipment from Hebei Huatao Group Ltd, represented in the UK by Jarshire



Huatao Group produces top quality belts used in the heating and tracking section of all types of corrugators and for all kinds of demanding applications.

Corrugator Belt Series

Model 1: Needle Corrugator Belt

- Thickness: 9-10mm
- Width range: 1400mm-2800mm
- Heat resistance: 200°C
- Weight: 5.5 kg/m²
- Suitable speed: 100-300m/min
- Seam: Hidden seam



Corrugating machines supported include:
BHS
AGNATI
MHI/MI
MARQUIP
TCY
ISOWA



Model 2: Woven Corrugator Belt

Suitable for the demands of high speed production. Widely used for heavy board and double wall.

- Thickness: 9mm
- Width range: 1400mm-3200mm
- Heat resistance: 220°C
- Weight: 7.5 kg/m²
- Suitable speed: 250m/min
- Seam: Hot jaw lacing with flocking
- Fasteners: Clipper with rubber



Model 3: Reinforced Edge Corrugator Belt


Specially designed for frequent changes of width. Suitable as a top belt with long lifetime. Excellent tear resistance.

- Thickness: 9mm
- Width range: 1400mm-3200mm
- Heat resistance: 240°C, edge up to 350°C
- Weight: 7.5 kg/m²
- Suitable speed: 200m/min
- Seam: Hot jaw lacing with flocking
- Fasteners: Clipper with rubber

Traction/take-up belt

Used for corrugated board transport over the single facer and for onward transport on the bridge and to the board deposit in the stacker.

- Material: 100% Polyester
- Thickness: 5-6mm
- Weight: 3.5 kg/m²
- Width: 600-2800mm
- Standard sizes: 600mm, 800mm, 1000mm, 1200mm, 1400mm, 1600mm
- Heat resistance: Under 130°C accepts short time pressure
- Tension: 40Kpa
- Minimum winding radius: R20(mm)




Corrugator belt seam features:



Hot clipper (jaw) with flocking

Safe and consistent with excellent running performance.

- Low noise emission
- Flocking surface protects the corrugated board with no marks
- No weakening of the fabric
- No contact of the clipper with the board heating plates and pressure loading system



Clipper with rubber coat

Low noise emission and resistance from tearing.

- Non-abrasion
- Rubber surface to protect the smooth corrugated board
- Rubber flat surface neither damages pressure device nor outer rubber of driving-roller
- Stabilises transmission
- Prevents heavy roll from jointing

JARSHIRE
CORRUGATING & BOARD

Contact Nick Jobson on
01753 825122 or
sales@jarshire.co.uk for information

BRAKES • CLUTCHES • CHUCKS • CONVEYORS • CORRUGATING ROLLS • CORRUGATOR BELTS
DRY-END PRODUCTION LINES • KNIVES • PACKAGING MACHINERY • REEL-SAVERS
REEL STANDS • ROLL AND REEL PUSHERS • ROLLER BEARINGS

SERVICING

Throughout the UK and Ireland, Jarshire provides an efficient on-site maintenance and service facility from fully equipped vans, 24 hours a day, seven days a week. Where appropriate, remote assistance from the manufacturer is available via a dedicated modem.